

DC Advertising pedestal series

Innovativeness

One charger with two output sockets
Business use with intelligent App control
Vandal resistant and anti-corrosion

Intelligent Control

Ethernet/4G/Wi-Fi communication all supported
OCPP communication protocol with CMS
Intelligent operation by App and cashless payment

Large screen advertising revenue

55"HDV 3500cd/m²
Remotely update AD content



Credit card payments
(Optional)



Model	ZECO60K-ADD4	ZECO120K-ADD5
Technical Features		
Charging Capacity	Up to 60KW	Up to 120KW
Input / Output Power	400VAC±10%-50/60Hz- 3phase	
Power Factor	≥0.98	
Efficiency	>95%	
Measuring Accuracy	level 0.5	
Output Voltage Range	CCS: 250~1000VDC	
Output Current Range	0-180A	0-250A
Communication	PLC (between charger & vehicle) Ethernet / 4G / OCPP 1.6J (Optional)	
User Interface	LCD 7 inch Touch Screen / RFID card and APP	
Versatility	EN / IEC 61851-1: 2019, EN / IEC 61851-23: 2014.	
Security Design	Over / under voltage protection, overload protection, current leakage protection, grounding protection, lightening surge protection	
DC Plugs	CCS2 Cable 5M*2.	
Energy Meter	CE certified or PTB (Optional)	
RCD	Type A or Type B (Optional)	
Advertising Display		
Mainboard	Android Based Quad-core	
RAM	2GB	
Storage	8GB, can extend to 32GB	
Video Format	MPG, MPG-1, MPG-2, MPG-4, AVI, MP4, TS, MKV, WMV	
Maximum Decoding Resolution	3480*2160	
Picture Format	GIF, JPEG, PNG, BMP	
Audio Output	2x10W	
Audio Format	MP3, 24bit linear PCM7.1	
Other Format	PDF / RSS, News / Weather-Forecast	
Network	Rj45 interface, Wifi, 4G, Option,	
The Update Way For Content	Network remote update, U disk update.	
Display Mode	Landscape / Portrait, Full Screen / Any Split Screen	
Program Upgrade	Remote upgrade, remote upgrade	
Timer Switch	Support any time period	
Panel Parameters	Panel Type	55 Inch LCD Panel
	Display area	1209*680mm
	Display ratio	16:9
	Backlight type	LED backlight
	Resolution	3480x2160
	Display color	16.7M
	Brightness	3500-cd/m²
	Contrast	3500:1
	View angle	178°(H) / 178°(V)
	Response time	6ms
	Life time	50000 hours
Physical Properties		
Warranty	3 years	
Protection	IP55 (Outdoor)	
Special Protection	Topple & fall down protection	
Cooling	Natural cooling	
Operating Temperature	-30℃ to +55℃	
Humidity	Max.95% (Non-Regulating)	
Dimensions	2310*1170*650 (L*W*H)	
Net Weight	280Kg	
Gross Weight	321Kg	