

MINI DC Series

30KW-40KW-60KW the best charging station
For EV fast charger

Friendly interface

7-inch touch screen LCD and ring LED offer good user display requirements for charging.

Simple control

It is easy to control on and off through the Bluetooth function of the mobile phone APP and RFID function.

Fast and Safety

40KW CCS type 2 plug, more efficient charging
IP54 protection level for outdoor installation.

Wide application

Compliant with OCPP 1.6 and above enables it to connect to the global EV charge management platform without additional integration and matching.



CCS2



CCS1



NACS(tesla)



GB/T



Credit card payments
(Optional)



Model	ZECO30K-D1	ZECO40K-D2	ZECO60K-D3
Technical features			
Max Power	Up to 30KW	Up to 40KW	Up to 60KW
Input/Output power	400VAC±10%-50/60Hz-3phase	400VAC±10%-50/60Hz-3phase	400VAC±10%-50/60Hz-3phase
Power factor	0.98		
Efficiency	>95%		
Measuring accuracy	Level 0.5		
Output voltage range	CCS: 300~1000VDC		
Output current range	0-100A	0-100A*2	0-200A*2
Communication	Ethernet/WIFI/4G/OCPP 1.6 Json (OCPP 2.0 optional)		
User interface	RFID card and APP		
Display	LCD 7 inch Touch Screen		
Versatility	IEC61851/IEC62196/ISO1511/DIN70121/EN61000-6-4:2007		
Energy Meter	CE certified		
RCD	Type A or Type B(optional)		
Security design	Over/under voltage protection, overload protection, current leakage protection, grounding protection, lightning surge protection		
DC Plugs	CCS2 Cable 5M	CCS2*2 Cable 5M	CCS2*2 Cable 5M
Physical properties			
Warranty	2 years		
Application place	Indoor/Outdoor		
Installation method	Wall mount, pedestal mount (optional)		
Sound noise	<55DB in all directions		
Operating temperature	-20 C to +50 C		
Humidity	Max.95%(non-regulating)		
Dimensions	670*460*270mm	770*560*206mm	900*650*260mm
Package Dimension	800*590*480mm	1010*720*510mm	1200*920*450mm
Net Weight	41Kg	75Kg	115Kg
Gross Weight	46Kg	78Kg	120Kg