

Twin Pedestal Series

Safe and Fast

One charger with two output sockets
Business use with intelligent App control
Vandal resistant and anti-corrosion

Simple and intelligent

Ethernet/4G/Wi-Fi communication all supported
OCPP communication protocol with CMS
Intelligent operation by App and cashless payment

Flexible Option

App operation or RFID authentication or plug and play
Customization with different color painting



Credit card payments
(Optional)



Model	ZECO14K-BK1	ZECO22K-BK2	ZECO44K-BK3
Technical features			
Charging capacity	Up to 14KW(7KW*2)	Up to 22KW(11KW*2)	Up to 44KW(22KW*2)
Input/Output power	230VAC±20%-50/60Hz-32A*2-1phase	400VAC±20%-50/60Hz-16A*2-3phase	400VAC±20%-50/60Hz-32A*2-3phase
RCD	30Ma RCD Type A and DC 6Ma RCD function or Type B(optional)		
Standby power	<5W		
Measuring accuracy	1%		
Energy Meter	MID certified		
OCPP	OCPP1.6 Json(OCPP2.0 optional)		
Communication	WIFI/Ethernet/4G(Optional)		
User interface	LED / LCD(3.5'') / RFID(mifare iso& IEC 14443A)		
Certificate/Compliance	CE / EN/IEC 61851-1:2017, EN/IEC 61851-21-2:2018		
Charging Interface	Type 2 socket*2 or Type 2 Gun *2 5M		
Special Protection	Over current protection, Residual current protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection		
Physical properties			
Warranty	2 years		
Protection	IP54, IK10,		
Enclosure	Galvanized steel		
Front Panel	Temper glass		
Installation	Floor-stand		
Cooling	Natural cooling		
Operating temperature	-30°C to +55°C		
Humidity	Max.95%(non-regulating)		
Product Dimensions	1200*290*230(L*W*H)mm		
Package Dimension	1320*480*430(L*W*H)mm		
Net Weight	30Kg	33Kg	35Kg
Gross Weight	45Kg	48Kg	50Kg