



## Super DC Series

**300-480KW** the best charging station  
For EV fast charger



### High Efficiency

One charger with two outputs, simultaneously charging  
Two CCS2/CCS1, NACS, GB/T DC connectors, with  
output up to 480kW Constant power from 150~1000V  
voltage, less heat with smaller current

### Intelligent Control

Ethernet/4G/ communication all supported  
OCPP1.6 communication protocol with CMS  
Intelligent operation by App and cashless payment

### Flexible Option

App operation or RFID authentication or plug and play  
High protection grade as IP54, with IP65 optional  
Optional POS terminal for contactless credit card  
payment

### Secure and Safe

Type A RCD for residual current protection  
PTB certified energy meter with accurate measurement  
DIN 70121 prepared for advanced feature of Plug&Charge

Model	ZECO300K-D9	ZECO360K-D10	ZECO400K-D11	ZECO480K-D12
Technical features				
Max Power	Up to 300KW	Up to 360KW with 2 gun Up to 350KW with 1 gun	Up to 400KW with 2 gun Up to 350KW with 1 gun	Up to 480KW with 2 gun Up to 350KW with 1 gun
Input Voltage	400VAC±10%-50/60Hz-3phase(CCS2 and GB/T) 480VAC±10%-50/60Hz-3phase(CCS1+NACS)			
Power factor	≥0.98			
Efficiency	>95%			
Measuring accuracy	Level 0.5			
Output voltage range	CCS: 150~1000VDC			
Output current range	0-250A 0-350A(optional)			
Communication	ISO15118 / DIN70121(between charger & vehicle) Ethernet/4G/OCPP 1.6J（TLS1.2）			
User interface	LCD 7 inch Touch Screen /RFID card and APP			
Versatility	EN/IEC 61851-1: 2019, EN/IEC 61851-23: 2014 ,UL 2202, UL2594			
Security design	Over/under voltage protection, overload protection, current leakage protection, grounding protection,lightening surge protection			
DC Plugs	Cable 5M			
Energy Meter	CE certified			
RCD	Type A			
Load balancing	Load balancing meter and CT(optional)			
Physical properties				
Warranty	2 years			
Cooling	Air cooled			
IP Level	IP54			
Sound noise	<70DB in all directions			
Operating temperature	-20℃ to +50℃			
Humidity	Max.95%(non-regulating)			
Dimensions	750*770*1850mm			
Package Dimension	800*850*1950(L*W*H)mm Wooden packing			