

Commercial Advertising AC charger 14KW-44KW



Innovativeness

One charger with two output sockets Business use with intelligent App control Vandal resistant and anti-corrosion

Intelligent Control

Ethernet/4G/Wi-Fi communication all supported OCPP communication protocol with CMS Intelligent operation by App and cashless payment

Large screen advertising revenue

55 " HDV 2500cd/m² Remotely update AD content



Model	ZECO-0140-AD1	ZECO-0220-AD2	ZECO-0440-AD3
Technical features			
Charging capacity	Up to 14KW(7KW*2)	Up to 22KW(11KW*2)	Up to 44KW(22KW*2)
Input/Output power	230VAC±20%-50/60Hz-32A*2-1phase	400VAC±20%-50/60Hz-16A*2-3phase	400VAC±20%-50/60Hz-32A*2-3phase
RCD	RCMU(Type A+ DC 6mA)/ Type B RCCB(Optional)		
Standby power	<5W		
Measuring accuracy	1%		
Energy Meter	MID certified		
OCPP	OCPP1.6 Json(OCPP2.0 optional)		
Communication	WIFI/ Ethernet/4G(Optional)		
User interface	LCD 5 inch Touch Screen/ RFID(mifare iso& IEC 14443A)		
Certificate/Compliance	CE/ FCC/ ROHS/ REACH/ IEC/ EN 61851-1, IEC/ EN61851-21-2, IEC/ EN 62955, En300328, EN 301489-1/-17, En62479		
Charging Interface	Type 2 socket*2 or Type 2 Gun *2 5M		
Special Protection	Over current protection, Residual current protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection , Over/ Under temperature protection		
Advertising display			
LCD screen	55" IPS 1920* 1080 16:9 HDV 2500cd/m²		
Application platform	Android 4.3 and above		
Communication	WIFI/ Ethernet/4G(Optional)		
Ad update	USB flash disk, SD card, wired network remote release		
Physical properties			
IP Level	IP55		
Special Protection	Topple & fall down protection		
Cooling	Natural cooling		
Operating temperature	-30℃ to +55℃		
Humidity	Max 95%(non-regulating)		
Product Dimension	920*290*1950mm(L*W*H)		
Package Dimension	450*1170*2110mm(L*W* H)		
Net Weight	201kg		
Gross Weight	320kg		