

Commercial Advertising DC charger 60KW-160KW



Intelligent Control

Ethernet / 4G / Wi-Fi communication all supported OCPP communication protocol with CMS Intelligent operation by App and cashless payment Large screen advertising revenue.

Innovativeness

One charger with two output sockets Business use with intelligent App control Vandal resistant and anti-corrosion

Large screen advertising revenue

43 "and 55 " HDV 2500cd/m² Remotely update AD content



Physical properties	
IP Level	IP55(outdoor)
Special Protection	Topple & fall down protection
Cooling	Natural cooling
Operating temperature	-30℃ to +55℃
Humidity	Max. 95%(non-regulating)
Dimensions	2310*1170*650(L*W* H)
Net Weight	280Kg
Gross Weight	321Kg

SPECIFICATION

Model	ZECO-0600-DCA1	ZECO-1200-DCA2	ZECO-1600-DCA3
Technical features			
Charging capacity	Up to 60KW	Up to 120KW	Up to 160KW
Input/Output power	400VAC±10%-50/60Hz- 3phase		
Power factor	≥0 .98		
Efficiency	>95%		
Measuring accuracy	level 0.5		
Output voltage range	CCS: 250~ 1000VDC		
Output current range	0-200A	0-250A	0-250A
Communication	PLC (between charger & vehicle) Ethernet / 4G / OCPP 1.6J(optional)		
User interface	LCD 7 inch Touch Screen / RFID card and APP		
Versatility	EN/ IEC 61851-1: 2019 , EN/ IEC 61851-23: 2014		
Security design	Over/under voltage protection, overload protection, current leakage protection, grounding protection, lightening surge protection		
DC Plugs	CCS2 Cable 5M*2		
Energy Meter	CE certified or PTB (optional)		
RCD	MCC B OR MCC B withtypeA(Optional)		
Advertising display			
Mainboard	Android based Quad-core		
RAM	2GB		
Storage	8GB, can extend to 32GB		
Video format	MPG, MPG-1, MPG-2, MPG-4,AVI, MP4, TS, MKV, WMV		
Maximum decoding	3480x2160		
Picture format	GIF,JPEG, PNG, BMP		
Audio output	2x10W		
Audio format	Mp3, 24bit linear PCM7.1		
Other format	PDF/ RSS, News/Weather-forecast		
Network	Rj45 interface, Wifi, 4G, Option		
The update way for	Network remote update, U disk update		
Display mode	Landscape/ Portrait, Full Screen/Any Split Screen		
Program upgrade	Remote upgrade, remote upgrade		
Timer switch	Support any time period		
Panel parameters			
Panel Type	55 inch LCD Panel		
Display area	1209*680mm		
Display ratio	0.672917		
Backlight type	LED backlight		
Resolution	3480x2160		
Display color	16 .7M		
Brightness	3500-cd/m2		
Contrast	3500:1		
View angle	178°(H) / 178°(V)		
Response time	6ms		
Life time	50000 hours		