



Innovativeness

One charger with two output sockets Business use with intelligent App control Vandal resistant and anti-corrosion.

Large screen advertising revenue

55"HDV 3500cd/m²
Remotely update AD content

Intelligent Control

Ethernet/4G/Wi-Fi communication all supported OCPP communication protocol with CMS Intelligent operation by App and cashless payment



POS Payment
Integration

SPECIFICATION

Model	ZECO-0600-DC1	ZECO-1200-DC2	ZECO-1600-DC3	ZECO-1800-DC4
Technical features				
Charging capacity	Up to 60KW	Up to120KW	Up to 160KW	Up to180KW
Input/Output power	400VAC±10%-50/60Hz-3phase(CCS2 and GB/T)/480VAC±10%-50/60Hz-3phase(CCS1)			
Power factor	≥0.98			
Efficiency	>95%			
Measuring accuracy	Level 0.5			
Output voltage range	CCS: 250~1000VDC			
Output current range	0-200A	0-250A		
Communication	ISO15118 / DIN70121(between charger & vehicle) Ethernet/4G/OCPP 1.6J			
User interface	LCD 7 inch Touch Screen /RFID card and APP			
Versatility	EN/IEC 61851-1: 2019, EN/IEC 61851-23: 2014 ,UL 2202, UL2594			
Security design	Over/under voltage protection, overload protection, current leakage protection, grounding protection,lightening surge protection			
DC Plugs	CCS1/CCS2/NACS/GBT Cable 5M *2			
Energy Meter	CE certified or MID (optional)			
Advertising display				
Mainboard	Android based Quad-core			
RAM	2GB			
Storage	8GB, can extend to 32GB			
Video format	MPG,MPG-1,MPG-2,MPG-4,AVI,MP4, TS,MKV,WMV			
Maximum decoding resolution	3480x2160			
Picture format	GIF,JPEG,PNG,BMP			
Audio output	2x10W			
Audio format	MP3,24bit linear PCM7.1			
Other format	PDF/RSS, News/Weather-forecast			
Network	RJ45 interface , Wifi , 4G(Optional)			
The update way for content	Network remote update, U disk update			
Display mode	Landscape/Portrait, Full Screen/Any Split Screen			
Program upgrade	Remote upgrade, remote upgrade			
Timer switch	Support any time period			
Panel Type	43inch LCD Panel			
Display area	1209*680mm			
Display ratio	16:9			
Backlight type	LED backlight			
Resolution	3480x2160			
Display color	16.7M			
Brightness	2000-cd/m2			
Contrast	2000:1			
View angle	178°(H) / 178°(V)			
Response time	6ms			
Life time	50000 hours			
Physical properties				
Warranty	2 years			
Protection	IP55(outdoor)			
Special Protection	Topple & fall down protection			
Cooling	Natural cooling			
Operating temperature	-30°C to +55°C			
Humidity	Max.95%(non-regulating)			
Product Dimensions	1750*840*500mm(L*W*H)			
Package Dimension	2310*1170*650mm(L*W*H)			
Net Weight	320Kg			
Gross Weight	361Kg			