

Commercial Advertising DC charger 60KW-240KW



Intelligent Control

Ethernet / 4G / Wi-Fi communication all supported OCPP communication protocol with CMS Intelligent operation by App and cashless payment Large screen advertising revenue.

Innovativeness

One charger with two output sockets Business use with intelligent App control Vandal resistant and anti-corrosion

Large screen advertising revenue

43 "and 55 " HDV 2500cd/m² Remotely update AD content



Physical properties	
IP Level	IP55(outdoor)
Special Protection	Topple & fall down protection
Cooling	Natural cooling
Operating temperature	-30°C to +55°C
Humidity	Max. 95%(non-regulating)
Product/Package DIM	840*592*2000mm(L*W* H)/ 1170*650*2310mm
Net Weight	280Kg
Gross Weight	321Kg

SPECIFICATION

Model	ZECO-0600 -DCA1	ZECO-0800 -DCA2	ZECO-1200 -DCA3	ZECO-1600 -DCA4	ZECO-2400 -DCA5
Technical features					
Charging capacity	Up to 60KW	Up to 80KW	Up to 120KW	Up to 160KW	Up to 240KW
Input/Output power	101A	135A	203A	270A	405A
Input/Output power	400VAC±10%-50/60Hz- 3phase				
Power factor	≥0 .98				
Efficiency	>95%				
Measuring accuracy	level 0.5				
Output voltage range	CCS: 200~ 1000VDC				
Output current range	100-200A	100-200A	0-250A	0-250A	0-250A
Communication	ISO15118 / DIN70121(between charger & vehicle) Ethernet/4G/OCPP 1.6J(WSS)/Modbus TCP				
User interface	LCD 7 inch Touch Screen / RFID card and APP				
Versatility	EN IEC 61851-1:2019/EN 61851-23:2014/EN 61851-24:2014/EN IEC 61851-21-2:2021/EN 301 489-1 V2.2.3:2019/EN 301 489-3 V2.3.2:2023/EN 300 330 V2.1.1:2017/EN 62311:2008/EN IEC 62311:2020 TUV CE				
Security design	Over/under voltage protection, overload protection, current leakage protection, grounding protection, lightening surge protection				
DC Plugs	CCS2 Cable 5M*2				
Energy Meter	CE certified / MID certified(Optional)				
MCCB	MCCB or RCCB (TypeA)				
Advertising display					
Mainboard	Android based Quad-core				
RAM	2GB				
Storage	8GB, can extend to 32GB				
Video format	MPG, MPG-1, MPG-2, MPG-4,AVI, MP4, TS, MKV, WMV				
Maximum decoding	3480x2160				
Picture format	GIF,JPEG, PNG, BMP				
Audio output	2x10W				
Audio format	Mp3, 24bit linear PCM7.1				
Other format	PDF/ RSS, News/Weather-forecast				
Network	Rj45 interface, Wifi, 4G, Option				
The update way for	Network remote update, U disk update				
Display mode	Landscape/ Portrait, Full Screen/Any Split Screen				
Program upgrade	Remote upgrade, remote upgrade				
Timer switch	Support any time period				
Panel parameters					
Panel Type	55 inch LCD Panel				
Display area	1209*680mm				
Display ratio	0.672917				
Backlight type	LED backlight				
Resolution	3480x2160				
Display color	16 .7M				
Brightness	3500-cd/m2				
Contrast	3500:1				
View angle	178°(H) / 178°(V)				
Response time	6ms				
Life time	50000 hours				