



## Commercial EV Wallbox 14KW-44KW

### Innovativeness

One charger with two output sockets  
Business use with intelligent App control  
Vandal resistant and anti-corrosion

### Intelligent Control

Ethernet/4G/Wi-Fi communication all supported OCPP communication protocol with CMS Intelligent operation by App and cashless payment

### Flexible option

Supports app operation, RFID authentication, and plug-and-play functionality. Customizable with different color options.



## SPECIFICATION

Model	ZECO-0140-T1	ZECO-0220-T2	ZECO-0440-T3
<b>Technical features</b>			
Charging capacity	Up to 14kw (7kw*2)	Up to 22kw (11kw*2)	Up to 44kw (22kw*2)
Input/Output power	230VAC±20%-50/60Hz -32A-1phase	400VAC±20%-50/60Hz- 16A-3phase	400VAC±20%-50/60Hz -32A-3phase
RCD	RCMU(Type A+ DC 6mA)/ Type B RCCB(Optional)		
Standby power	<5W		
Measuring accuracy	1%		
Energy Meter	MID certified		
OCPP	OCPP1.6 Json(OCPP2.0 optional)		
Communication	WIFI / Ethernet / 4G(Optional)		
User interface	LCD 5 inch Touch Screen/RFID(mifare iso&IEC14443A)		
Certificate/Compliance	CE/ FCC/ ROHS/ REACH/ IEC/ EN 61851-1, IEC/ EN61851-21-2, IEC/ EN 62955, En300328, EN 301489-1/-17, En62479		
Charging Interface	Type 2 socket* 2 or Type 2 Gun*2/5MCable		
Special Protection	Over current protection, Residual current protection, Ground protection, Surge protection, Over/ Under voltage protection, Over/ Under frequency protection, Over/ Under temperature protection		
<b>Physical properties</b>			
Protection	IP55 , IK10		
Enclosure	Galvanized steel		
Front Panel	Tempered glass		
Installation	Wall-mount/ Pole-mount		
Cooling	Natural cooling		
Operating temperature	-30°C to +55°C		
Humidity	Max 95%(non-regulating)		
Product Dimensions	334*151*502.6( L*W* H ) mm		
Package Dimension	405*365*605( L*W* H ) mm		
Net Weight	14.12Kg	14.12Kg	14.12Kg
Gross Weight	15.25Kg	15.25Kg	15.25Kg